

## RENDER COVERAGE CHART

**TABLE 1 - COVERAGE OF RENDER IN M<sup>2</sup> OVER A SOLID SUBSTRATE (NO ALLOWANCE MADE FOR WASTE)**

**RENDER TYPES**

THICKNESS (mm)	STANDARD BASECOAT (BPBASCOR)	FIBRE BASECOAT (BPFIBBASCOR)	LIGHTWEIGHT BASECOAT (BPBASCORLT)	STANDARD TOPCOAT (BPRENCOR)	DASH RECEIVER (BPDASHCOR)	LIGHTWEIGHT TOPCOAT (BPDASHCORLT)	ROUGHCAST TOPCOAT (BPWETCAST)	SPRAY BASECOAT (BPBASPRAY)	SPRAY TOPCOAT (BPDASHSPRAY)
3	4.17	4.17	6.94	4.17	5.56	8.33	-	5.56	5.56
4	3.13	3.13	5.21	3.13	<b>4.17 **</b>	6.25	-	4.17	4.17
5	2.50	2.50	4.17	2.50	3.33	5.00	-	3.33	3.33
6	2.08	2.08	3.47	2.08	2.78	4.17	-	2.78	2.78
7	1.79	1.79	2.98	1.79	2.38	3.57	-	2.38	2.38
8	1.56	1.56	2.60	<b>1.56</b>	<b>2.08</b>	<b>3.13</b>	<b>1.89</b>	2.08	<b>2.08</b>
9	1.39	1.39	2.31	1.39	1.85	2.78	-	1.85	1.85
10	1.25	1.25	2.08	<b>1.25 *</b>	1.67	2.50	-	1.67	1.67
11	1.14	1.14	1.89	1.14	1.52	2.27	-	1.52	1.52
12	<b>1.04</b>	<b>1.04</b>	<b>1.74</b>	1.04	1.39	2.08	-	<b>1.39</b>	1.39
13	0.96	0.96	1.60	0.96	1.28	1.92	-	1.28	1.28
14	0.89	0.89	1.49	0.89	1.19	1.79	-	1.19	1.19
15	0.83	0.83	1.39	0.83	1.11	1.67	-	1.11	1.11

### BASECOATS

Standard Basecoat = 2.0kg/mm thick/m<sup>2</sup> - 25 kg Bag  
 Fibre Basecoat = 2.0kg/mm thick/m<sup>2</sup> - 25 kg Bag  
 Lightweight Basecoat = 1.2kg/mm thick/m<sup>2</sup> - 25 kg Bag

\* For Scratch finishes only

\*\* To be used as a 'buttercoat' for the Roughcast System

### TOPCOATS

Rencor/Rensil = 2.0kg/mm thick/m<sup>2</sup> - 25 kg Bag  
 Dash Receiver = 1.5kg/mm thick/m<sup>2</sup> - 25 kg Bag  
 Fibre Dash Receiver = 2.0kg/mm thick/m<sup>2</sup> - 25 kg Bag  
 Lightweight = 1.0kg/mm thick/m<sup>2</sup> - 25 kg Bag  
 Wetcast (Roughcast) = 1.65kg/mm thick/m<sup>2</sup> - 25 kg Bag  
 Spray Renders = 1.5kg/mm thick/m<sup>2</sup> - 25 kg Bag

Date: 1st May 2006